

SAMHWA PAINT		<b>MATERIAL SAFETY DATA SHEET</b>	Date of Issue		2013.11.26	
CODE			Renewal Date		2016.10.01	
	3730844		Renewal No.		2	Page 1 / 6

## 1. CHEMICAL PRODUCT INFORMATION

Product Name	SMA300	Color	
Chemical description	Thinner		
Application	Drying Accelerator		
Hazard	Harmful / Flammable Liquid		
Manufacture	SAMHWA PAINT IND.CO.,LTD.	Telephone NO.	82-31- 499 - 0394
Address	178, Byeolmang-ro, Danwon-gu, Ansan-si, Gyeonggi-do, Korea		

## 2. HAZARDS IDENTIFICATION

### 1. Classification of the substance

- ① FLAMMABLE LIQUIDS - category 2
- ② CARCINOGENICITY - category 1B
- ③ ASPIRATION HAZARD - category 1
- ④ SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - category 2

### 2. GHS warning label elements, including precautionary statements



① Symbol :

② Signal word : Danger

③ Hazard statements : Highly flammable liquid and vapour  
 May cause cancer  
 May cause damage to organs(Specific target organ-stomach, lung, heart) through prolonged or repeated exposure  
 May be fatal if swallowed and enters airways

④ Precautionary statements :

Prevention- Do not handle until all safety precautions have been read and understood.  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 Ground/bond container and receiving equipment.  
 Use explosion-proof electrical/ventilating/lighting/etc/ equipment.  
 Obtain special instructions before use.  
 Do not breathe dust/fume/gas/mist/vapours/spray.  
 Keep container tightly closed.  
 Take precautionary measures against static discharge.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 Use only non-sparking tools.

Response- Do NOT induce vomiting.  
 IF exposed or concerned: Get medical advice/attention.  
 In case of fire: Use fire extinguisher for extinction.  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Get medical advice/attention if you feel unwell.  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Storage- Store in a well-ventilated place. Keep cool.  
 Store locked up.

Disposal- Dispose of contents/container to relate laws and regulations.

SAMHWA PAINT		<b>MATERIAL SAFETY DATA SHEET</b>	Date of Issue		2013.11.26	
CODE			Renewal Date		2016.10.01	
3730844			Renewal No.		2	Page 2 / 6

### 3. CHEMICAL COMPOSITION

Chemical Name	CAS NO.	Portion(%)	Remarks
Dibutyltin dilaurate	77-58-7	0 ~ 1%	
Solvent naphtha (petroleum), light arom.	64742-95-6	61 ~ 70%	
Propylene glycol	57-55-6	1 ~ 10%	
1,4-Diazabicyclo[2.2.2]octane	280-57-9	0 ~ 1%	
Xylene	1330-20-7	6 ~ 10%	
Propylene glycol methyl ether acetate	108-65-6	11 ~ 20%	

### 4. HEALTH HAZARD INFORMATION

1. Eye contact  
Wash off immediately with plenty of water, also under the eyelids, for at least 20 minutes.  
Call a physician immediately.
2. Skin contact  
Remove the contaminated clothes and the skin will be washed with water and soap.  
Do not use solvents.
3. Inhalation  
Move to fresh air and if he/she not breathes perform artificial respiration.  
Consult a physician if necessary.
4. Ingestion  
Do not induce vomiting unless it is indicated by medical personnel.  
Never give anything by oral tract to an unconscious. Get medical attention if symptoms appear.
5. Note to physician  
Very small quantities of the product reached in lungs may be fatale. Ingestion of the product may cause chemical irritation that may diffuse to lungs and cause edema. Check carefully the victim and apply intubations in all ingestion cases for all important amounts.

SAMHWA PAINT		<b>MATERIAL SAFETY DATA SHEET</b>	Date of Issue		2013.11.26	
			Renewal Date		2016.10.01	
CODE	3730844		Renewal No.		2	Page

### 5. FIRE FIGHTING MEASURES

- Flash point : 19.3 °C
- Ignition temp : Not determined
- Upper explosion limit / Lower explosion limit : Not determined
- The Fire Service Act : Fourth grade 1st. Petroleum
- Fire extinguisher : CO<sub>2</sub>, Powder, Halogen Fire extinguisher and Sand etc.
- Fire and explosion Method of extinguishing and equipment:  
Wear suitable protective equipment Use product with caution around heat, sparks, pilot lights, static electricity, and open flame.  
Due to vapor is heavier than air, keep the distance from the ignition source pour into the fresh air.  
Remove promptly flammable material. Put out a fire at once with prepared fire extinguisher.
- Hazardous materials in combustion:  
Could be generated complexed mixture like solid and gas containing CO, SO<sub>2</sub> etc.  
Unidentified organic and inorganic compound.
- Extinguishing method which must not used for safety : Not applicable

### 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions  
Evacuate useless personnel, isolate the heat and flame sources, ventilate and wet the area if is possible.  
All personnel must be protected against vapours inhalation and against skin and eyes contact.
- Methods for cleaning up  
Absorb with dry earth, sand or other non-combustible material and precede according decontamination regulation.  
Recovered product will be stored in metallic drums with removable lid or metallic containers, which will be sent to incineration.
- Environmental precautions  
Do not let the product to reach water, drain and earth. Prevent the extending in soil.  
Prevent entry into sewers, basements or confined areas; dike if needed

### 7. HANDLING AND STORAGE

- Handling  
Avoid contact with skin or eyes. Use only up well-ventilated areas.  
Avoid breathing vapor. Do not take internally. Take precautionary measures against static is charges.
- Storage  
The product must be kept in original container tightly closed. Store between 5~35°C in dry, well-ventilated place away from source of heat, ignition and direct sunlight.  
Solvent vapours are heavier than air and spread along floors. Vapours may form explosive mixtures. No smoking.
- Other precautions  
Emergency showers and eye wash stations should be readily accessible.  
Adhere to work practice rules established by government regulations

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 1. Exposure limit values

Chemical Name	Cas No	Interior provision	ACGIH
Dibutyltin dilaurate	77-58-7	TWA : 0.1 mg/m <sup>3</sup>	TWA 0.1 mg/m <sup>3</sup>
Solvent naphtha (petroleum), light arom.	64742-95-6	No data	No data
Propylene glycol	57-55-6	No data	No data
1,4-Diazabicyclo[2.2.2]octane	280-57-9	No data	No data

SAMHWA PAINT		<b>MATERIAL SAFETY DATA SHEET</b>	Date of Issue		2013.11.26	
			Renewal Date		2016.10.01	
CODE	3730844		Renewal No.		2	Page

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

1. Exposure limit values

Chemical Name	Cas No	Interior provision	ACGIH
Xylene	1330-20-7	TWA : 100 ppm 435 mg/m <sup>3</sup> STEL : 150 ppm 655 mg/m <sup>3</sup>	TWA 100 ppm
Propylene glycol methyl ether acetate	108-65-6	No data	No data

2. Environmental exposure control

Technical conditions regarding atmosphere protection. Determination of pollutants emission produced by stationary sources rules.

3. Respiratory protection: In case of insufficient ventilation, wear suitable respiratory equipment

4. Eye protection: Wear eye/face protection such as chemical goggles or face shield

5. Hand protection: For prolonged or repeated contact use solvent protective gloves. Barrier reams may help to protect the exposed areas of hand. However they should not be applied once exposure has occurred. Hand should be washed after contact

6. Skin protection: Personnel should wear protective clothing and antistatic footwear.

7. Additional: Before eating, drinking, or smoking, wash face and hands thoroughly with soap and water

### 9. PHYSICAL AND CHEMICAL PROPERTIES

- |  |                                     |
|--|-------------------------------------|
| 1. Appearance : colorless and transparent liqu | 8. Oxidising properties : No data   |
| 2. Odor : solvent specific                     | 9. Vapor pressure : No data         |
| 3. pH : Not applicable                         | 10. Specific gravity : 0.897        |
| 4. Solubility : Water-insoluble                | 11. Partition coefficient : No data |
| 5. Boiling point : No data                     | 12. Vapor density : No data         |
| 6. Melting point : No data                     | 13. Viscosity(25°C) : No data       |
| 7. Explosive properties : No data              | 14. Molecular weight : No data      |

### 10. STABILITY AND REACTIVITY

1. Chemical stability

The product is stable if is kept in original recipient and according with recommendation.

2. Condition to avoid

Avoid all possible sources of heat, electrostatic discharges, ignition(spark or flame).

Avoid storage at temperature higher than 35°C and direct exposure in the sunlight.

3. Materials to avoid

Strong oxidative substances, strong acid, and alkaline solutions may give exothermic reactions in contact with this product.

4. Hazardous decomposition products

Thermo oxidative decomposition gives carbon monoxide, carbon dioxide, nitrogen oxides and a dense smoke, which contain other unidentified decomposition products. If this product is heated up to its decomposition temperature may lead to explosion.

SAMHWA PAINT		<b>MATERIAL SAFETY DATA SHEET</b>	Date of Issue		2013.11.26	
			Renewal Date		2016.10.01	
CODE	3730844		Renewal No.		2	Page

## 11. TOXICOLOGICAL INFORMATION

### 1. Toxicity Information

Chemical Name	LD50.Oral	LD50.Skin	LD50.Inhalation (gas)	LD50.Inhalation (vapour)	LD50.Inhalation (mist)
Dibutyltin dilaurate	LD50 = 58 mg/kg Rat	LD50 = 777 mg/kg rabbit	Mist LC50 = 0.059 ~ 22 mg/kg Rat	Mist LC50 = 0.059 ~ 22 mg/kg Rat	Mist LC50 = 0.059 ~ 22 mg/kg Rat
Solvent naphtha (petroleum), light arom.	LD50 = 8400 mg/kg Rat	LD50 > 2000 mg/kg Rabbit	Mist LC50 = 3400 ppm 4 hr Rat	Mist LC50 = 3400 ppm 4 hr Rat	Mist LC50 = 3400 ppm 4 hr Rat
Propylene glycol	LD50 = 2000 mg/kg Rat	LD50 > 16000 mg/kg Rabbit	No data	No data	No data
1,4-Diazabicyclo[2.2.2]octane	LD50 = 700 mg/kg Rat	LD50 > 2000 mg/kg Rat	Steam LC50 > 20.2 mg/l 1 hr Rat	Steam LC50 > 20.2 mg/l 1 hr Rat	Steam LC50 > 20.2 mg/l 1 hr Rat
Xylene	LD50 4300 mg/kg Rat	LD50 4350 mg/kg Rabbit	LC50 47653 mg/l 4 hr rat	LC50 47653 mg/l 4 hr rat	Steam LC50 6700 ppm 4 hr Rat
Propylene glycol methyl ether acetate	LD50 = 8532 mg/kg Rat	LD50 > 5000 mg/kg Rabbit	Steam LC50 = 4345 ppm 6 hr Rat	Steam LC50 = 4345 ppm 6 hr Rat	Steam LC50 = 4345 ppm 6 hr Rat

## 12. ECOLOGICAL INFORMATION

### 1. Ecological Information

Chemical Name	LC50.fish	LC50.water fleas	LC50.algae
Dibutyltin dilaurate	LC50 > 3 mg/l 96 hr Brachydanio	EC50 > 0.21 mg/l 48 hr Daphnia magna	EC50 > 0.56 mg/l 72 hr Other
Solvent naphtha (petroleum), light arom.	LC50 = 9.22 mg/l 96 hr	EC50 = 6.14 mg/l 48 hr Daphnia magna	EC50 = 19 mg/l 72 hr
Propylene glycol	LC50 = 710 mg/l 96 hr	EC50 > 1000 mg/l 48 hr Daphnia magna	EC50 > 1000 mg/l 72 hr
1,4-Diazabicyclo[2.2.2]octane	LC50 > 100 mg/l 96 hr Cyprinus	EC50 > 92 mg/l 48 hr Daphnia magna	EC50 = 110 mg/l 72 hr Other
Xylene	LC50 3.3 mg/l 96 hr	LC50 190 mg/l 96 hr	No data
Propylene glycol methyl ether acetate	LC50 ≥ 100 mg/l 96 hr Oryzias	EC50 = 373 mg/l 48 hr Daphnia magna	EC50 ≥ 1000 mg/l 72 hr

2. Soil mobility : Not known

3. Persistence and degradability

There is no specific data available on the product itself. The product should not be allowed to enter drains or watercourses or be deposited where they can affect ground or surface waters.

4. Potential bioaccumulation : Be possible.

## 13. DISPOSAL CONSIDERATION

1. Relevant insurance of legislation

Dispose of in accordance with local regulations

2. Waste removal measures

Waste must be disposed of in accordance with state and local environmental regulations.

3. Direction for the waste disposal

Preferred options for disposal are recycling, incineration with energy recovery, and landfill.

SAMHWA PAINT		<b>MATERIAL SAFETY DATA SHEET</b>	Date of Issue		2013.11.26	
CODE			Renewal Date		2016.10.01	
3730844			Renewal No.		2	Page

### 14. TRANSPORT INFORMATION

1. Classification by shipping transportaiton dangerous substance and regulation of storage :
2. Direction for transport  
The product must be kept in original container tightly closed and transport at normal temperature.
3. International Martitie Dangerous Goods Code  
U.N Number : 1263  
Shipping name : Paint  
Hazard class : 3  
Packing group : 2
4. Marine pollutant : Not Applicable
5. Special precautions for user related to transport or transportation measures
  - Ems FIRE SCHEDULE : F-E
  - EmS SPILLAGE SCHEDULE : S-E

### 15. REGULATORY INFORMATION

1. Article of KOREA OCCUPATIONAL SAFETY \_HEALTY AGENCY : Not determined.
2. Article of Harmful Chemical Substance : Not applicable
3. Classify of The Fire Service Act : Fourth grade 1st.Petroleum

### 16. OTHER INFORMATION

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the data of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release is not to be considered a warranty or quality specification

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

This information is based on technical information believed to be reliable. It is subject to revision as additional knowledge and experience is gained.